

24 Channels Lighting Console

LT-24 24 Channels



Main Features

- High-bright LCD screen, displayed in English or Chinese
- 24channels, Patching to 512 DMX channels
- 2-preset (wide) mode or memory sub-master mode
- 12 sub-masters or 24 preset faders in wide mode, each with flash button and LED indicator
- 10 pages of memories with 24 memory sub-masters each page
- 16 effects memorized, including 6 effects user-defined
- External IC memory card, internal Ferroelectric Nonvolatile RAM storage
- DMX 512 output on 5 pin XLR connector, opto-isolated protection

Ordering Information

Cat NO	Description
303001	LT-24

Technique Parameters

- Power supply: 230V±10% 50/60HZ

Mechanical Data

- Dimensions (mm): 480(W) × 91(H) × 315(D)
- Net weight: 7kg
- Packing Dimensions (mm): 530(W) × 220(H) × 330(D)
- Gross weight: 8kg

Operation Environment

- Temperature: 0~37
- Humidity Range: 0~95% non condensing

BEIJING STARLIGHT ELECTRONICS CO.,LTD.

Address: NO. 7 Xingguang Lane, Xihongmen Town, Daxing District, Beijing 100162

Tel: +86 10 6025 9548, 6025 9546 **Fax:** +86 10 6025 9757

E-mail: mail@lightspace.com.cn


www.lightspace.com.cn

LIGHTSPACE®

24 Channels Lighting Console

LT-24 24Channels

Front panel layout



Connector layout



BEIJING STARLIGHT ELECTRONICS CO.,LTD.

Address: NO. 7 Xingguang Lane, Xihongmen Town, Daxing District, Beijing 100162

Tel: +86 10 6025 9548, 6025 9546 Fax: +86 10 6025 9757

E-mail: mail@lightspace.com.cn

www.lightspace.com.cn

LIGHTSPACE®